



# BOLT PRODUCTS INC



## UniClamp®

*The UniClamp® provides constant, leak proof prevention for low pressure applications. The wide band width insures improved clamping action without hose damage. This is a true low cost solution for high volume production..*

Part Series	Standard Pack	Clamp Size		Hose OD Installed		Max Clamp Diameter (free)		Min Clamp Diameter (expanded)	
		Inches	MM	Inches	MM	Inches	MM	Inches	MM
5503	40,000	0.21	5.3	0.230	5.8	0.210	5.3	0.250	6.4
3173	18,000	0.24	6.1	0.280	7.1	0.240	6.1	0.300	7.6
6044	40,000	0.25	6.4	0.280	7.1	0.240	6.1	0.300	7.6
5005	25,000	0.30	7.6	0.310	7.9	0.301	7.6	0.345	8.8
5006	15,000	0.32	8.1	0.380	9.7	0.321	8.2	0.405	10.3
2562	18,000	0.34	8.6	0.380	9.7	0.335	8.5	0.410	10.4
5073	20,000	0.38	9.7	0.410	10.4	0.375	9.5	0.450	11.4
5007	15,000	0.41	10.4	0.440	11.2	0.405	10.3	0.485	12.3
5075	10,000	0.43	10.9	0.470	11.9	0.430	10.9	0.515	13.1
4720	15,000	0.45	11.4	0.490	12.2	0.450	11.4	0.520	13.2
5173	13,000	0.38	9.7	0.410	10.4	0.375	9.5	0.450	11.4
5008	8,000	0.46	11.7	0.500	12.7	0.460	11.7	0.545	13.8
5077	8,000	0.49	12.4	0.530	13.5	0.490	12.4	0.573	14.6
5078	8,500	0.50	12.7	0.560	14.2	0.500	12.7	0.621	15.8
5009	8,000	0.52	13.2	0.560	14.2	0.520	13.2	0.605	15.4
5079	7,000	0.54	13.7	0.590	15.0	0.540	13.7	0.650	16.5
5279	11,000	0.54	13.7	0.590	15.0	0.540	13.7	0.650	16.5
5010	7,000	0.58	14.7	0.630	16.0	0.583	14.8	0.668	17.0
5082	8,500	0.58	14.7	0.690	17.5	0.583	14.8	0.720	18.3
5281	5,000	0.61	15.5	0.660	16.8	0.620	15.7	0.725	18.4
5081	8,000	0.62	15.7	0.660	16.8	0.620	15.7	0.725	18.4
5084	5,000	0.65	16.5	0.750	19.1	0.645	16.4	0.828	21.0
5011	6,000	0.66	16.8	0.690	17.5	0.655	16.6	0.750	19.1
4320	6,000	0.69	17.5	0.720	18.3	0.685	17.4	0.775	19.7
5012	7,000	0.69	17.5	0.720	18.3	0.685	17.4	0.775	19.7
5013	3,500	0.75	19.1	0.810	20.6	0.750	19.1	0.900	22.9



# BOLT PRODUCTS INC



## UniClamp®

The UniClamp® provides constant, leak proof prevention for low pressure applications. The wide band width insures improved clamping action without hose damage. This is a true low cost solution for high volume production..

Part Series	Standard Pack	Clamp Size		Hose OD Installed		Max Clamp Diameter (free)		Min Clamp Diameter (expanded)	
		Inches	MM	Inches	MM	Inches	MM	Inches	MM
5014	3,000	0.81	20.6	0.880	22.4	0.810	20.6	0.970	24.6
5015	2,500	0.86	21.8	0.940	23.9	0.860	21.8	1.030	26.2
5016	2,500	0.91	23.1	1.000	25.4	0.910	23.1	1.080	27.4
5093	3,600	0.95	24.1	1.030	26.2	0.950	24.1	1.130	28.7
5017	2,500	0.97	24.6	1.060	26.9	0.970	24.6	1.180	30.0
5018	3,000	1.04	26.4	1.130	28.7	1.040	26.4	1.240	31.5
5019	2,500	1.10	27.9	1.190	30.2	1.100	27.9	1.280	32.5
5098	3,400	1.10	27.9	1.280	32.5	1.100	27.9	1.280	32.5
5020	2,500	1.18	30.0	1.250	31.8	1.180	30.0	1.450	36.8
5024	2,000	1.44	36.6	1.500	38.1	1.350	34.3	1.670	42.4
4073	1,800	1.45	36.8	1.630	41.4	1.450	36.8	1.800	45.7
7401	5	Clamp pliers							

## Universal Metal Part Numbers

Base P/N      Finish  
 XXXX      -      XXX

Finish	Description	Advantages	SS Corrosion Rating
103	Phosphate, 2 coats Olive Drab Paint	Cost effective, Moderate SS	96 Hours
131	Phosphate, 2 coats Black Paint	Cost effective, Moderate SS	96 Hours
132	Phosphate, 2 coats Metallic Paint	Cost effective, Moderate SS	96 Hours
133	Phosphate, 2 coats Green Paint	Cost effective, Moderate SS	96 Hours
134	Phosphate, 2 coats Red Paint	Cost effective, Moderate SS	96 Hours
136	Phosphate & Yellow Paint	Cost effective, Moderate SS	40 Hours
324	2 Coats Geomet (Black finish)	High SS resistance, hex-free	480 Hours
328	2 Coats Geomet (Gray finish)	High SS resistance, hex-free	480 Hours