



RING NO.	SHAFT		GROOVE SIZE			RING DIMENSIONS					SUPPLEMENTARY DATA			
	DIAMETER (mm)		DIMENSIONS			No. Of Prongs	THICKNESS	WEIGHT Per 1000 Pcs.	Min. Distance	THRUST LOAD	EDGE MARGIN	D1	N	Y
	Ds	TOL.	Dg	Tol.	W Min.									
DTX-1.5	1.5		1.40		0.4	1.40	6.0	3	0.25	0.040	1.5	100	1.0	
DTX-2.0	2.0	+0,00	1.90	-0,060	0.4	1.85	6.5	3	0.25	0,042	1.5	150	1.0	
DTX-3.0	3.0	-0,060	2.90		0.4	2.80	8.0	4	0.25	0,066	1.5	200	1.0	
DTX-3.5	3.5		3.40		0.5	3.30	8.2	4	0.40	0,104	2.0	210	1.0	
DTX-4.0	4.0	+0,00	3.90	-0,075	0.4	3.80	9.0	4	0.25	0,078	2.0	220	1.0	
DTX-5.0	5.0	-0,075	4.90		0.4	4.80	10.0	4	0.25	0,082	2.0	230	1.0	
DTX-6.0	6.0		5.90		0.4	5.80	11.0	4	0.25	0,094	2.5	240	1.5	
DTX-7.0	7.0		6.90		0.4	6.80	12.0	6	0.25	0,110	2.5	250	1.5	
DTX-8.0	8.0	+0,00	7.85	-0,090	0.4	7.75	13.0	6	0.25	0,122	2.5	250	1.5	
DTX-9.0	9.0	-0,090	8.85		0.6	8.75	14.0	6	0.30	0,208	2.5	300	1.5	
DTX-10.0	10.0		9.85		0.6	9.75	16.0	6	0.30	0,232	3.0	320	1.5	
DTX-12.0	12.0		11.85		0.6	11.70	18.0	6	0.30	0,255	3.0	350	1.5	
DTX-14.0	14.0		13.80	-0,110	0.6	13.70	20.5	6	0.30	0,310	3.0	400	1.5	
DTX-15.0	15.0	+0,00	14.80		1.0	14.60	23.0	8	0.50	0,750	3.0	600	2.0	
DTX-16.0	16.0	-0,110	15.80		1.0	15.60	24.5	8	0.40	0,710	3.0	700	2.0	
DTX-17.0	17.0		16.80		1.0	16.60	26.0	8	0.50	0,950	3.5	800	2.0	
DTX-18.0	18.0		17.80		1.0	17.60	27.0	8	0.40	0,810	3.5	850	2.0	
DTX-19.0	19.0		18.80		1.0	18.60	28.0	8	0.50	0,950	3.5	900	2.0	
DTX-20.0	20.0		19.75		1.0	19.50	29.0	8	0.50	1,090	3.5	950	2.0	
DTX-22.0	22.0		21.75		1.0	21.50	31.0	8	0.50	1,150	3.5	1000	2.0	
DTX-23.0	23.0	+0,00	22.75	-0,130	1.0	22.50	31.5	8	0.50	1,220	4.0	1050	2.0	
DTX-25.0	25.0	-0,130	24.75		1.0	24.50	34.0	8	0.50	1,490	4.0	1100	2.0	
DTX-28.0	28.0		27.75		1.0	27.50	37.0	8	0.50	1,550	4.0	1200	2.0	
DTX-30.0	30.0		29.75		1.0	29.50	40.0	8	0.50	1,630	4.0	1300	2.0	
DTX-35.0	35.0	+0,00	34.75		1.0	34.50	46.0	8	0.50	2,100	4.0	1400	2.0	
DTX-45.0	45.0	-0,160	44.75		1.5	44.50	60.0	8	0.50	2,700	4.0	1500	2.0	

ALL DIMENSIONS IN MILLIMETERS.

TABLE 1: HARDNESS RANGES-ROTOR CLIP
STAINLESS STEEL RINGS (PH 15-7 MO)

RING	SIZE RANGE	SCALE	ROCKWELL HARDNESS
DTX	1,5-45,0	15N	82.5-86

TABLE 2: HARDNESS RANGES-ROTOR CLIP
CARBON STEEL RINGS (SAE 1060-1090)

RING	SIZE RANGE	SCALE	ROCKWELL HARDNESS
DTX	1,5-45,0	15N	83-85.5